
SENSO Bridge

Datasheet



SENSO Bridge is a signal repeater by means of which the signal coverage between SENSO devices can be significantly increased. It receives signals from SENSO transmitters and re-transmits them to SENSO receivers. Activation of repeater is accompanied with color LED light guide. Internal rechargeable battery allows for operation for 24 hours in a power cut.

Controls and indicators

- 1 Light guide
- 2 Test button
- 3 Battery charge indicator
- 4 Power supply microUSB
- 5 Anti-skid legs

Size and weight

Height: 32 mm / 1.25 inch Width: 87 mm / 3.42 inch Depth: 87 mm / 3.42 inch Weight (net): 98 g / 3.45 oz

In the box

SENSO Bridge repeater SENSO S-Wallmount Power adapter USB-microUSB cable User manual

General data

Specifications:

- Material: ABS plastic
- Radio frequency: 433.92 MHz
- Coverage: up to 100 m, depending on building's characteristics.
- Light guide: 7 colors
- Intrusion and water protection: IP 20 Battery charge indication:
- battery charge mulcation.
- Red blink battery empty
- Orange battery charging
- Green battery fully charged Environmental requirements:
- Temperature: from 0°C to 40°C

Power management

SENSO Bridge is powered by the mains through a power adapter. It comprises a backup built-in battery.

Battery:

Type: Li-Pol, rechargeablePosition: non-replaceable

Voltage: 3.7 VCapacity: 550 mAh

Estimated recharging time: 8 hours

Operating time in a power cut after a full charge:
 24 hours

Power supply:

Input: 100-240V AC 50 HzOutput: 5V DC 2100 mA

Power consumption: active ≤ 50 mA

Accessories (available separately)

SENSO S-Tablestand

Regulatory and standards

Radio equipment: 2014/53/EU RED

directive

SRD:

Safety: EN 62368-1:2014/A11:2017

EMC: EN 301 489-1

EN 301 489-3 EN 300 220-1

EN 300 220-2



€ 1299